NEWTONIETH FOWER

POWER PACK 60

| ENGINE | CUMMINS | \$3.8- G7 |
|--------------|----------|------------------|
| | | |
| ALTERNATOR | STAMFORD | UCI224E |
| ENGINE SPEED | 1500 | RPM |
| POWER PRIME | 3PH 50HZ | 60 KVA |





STAMFORD®

| ENGINE | CUMMINS |
|----------------------|----------------------------|
| FUEL | DIESEL |
| GOVERNER | MECHANICALLY GOVERNED |
| CYLINDERS | 4 |
| ASPIRATION | TURBO CHARGED INTER COOLED |
| DISPLACEMENT | 3.8 LITRES |
| COOLING SYSTEM | WATER COOLED |
| EMISSION | EU STAGE II |
| ENGINE POWER STANDBY | 64.9 KWM @ 1500RPM |
| ENGINE POWER PRIME | 59.6 KWM @ 1500 RPM |

| ALTERNATOR | STAMFORD UCI224E |
|----------------------|---------------------------------------|
| BASELOAD POWER | 60 KVA; 50HZ; 3PH @ 40°C |
| CONTINUOUS POWER | 60 KVA; 50HZ; 3PH @ 40°C |
| STAND BY POWER | 65 KVA; 50HZ; 3PH @ 40°C |
| VOLTS | AVR CONTROLLED |
| EXECUTION | BRUSHLESS |
| OVERLOAD (LONG TERM) | 1 HOUR IN A 6 HOUR PERIOD @110% RATED |

WWW.NEWTONTECHPOWER.CO.ZA

602 MOOIPLAATS PRETORIA

TEL +27 (0) 824432297 FAX +27 (0) 866111090

SALES@NEWTONTECHPOWER.CO.ZA

| FUEL CONSUMPTION | |
|--------------------|-----------|
| 50% OF PRIME POWER | 6.1 L/PH |
| 75% OF PRIME POWER | 11 L/PH |
| PRIME POWER | 14.7 L/PH |